

Aquatix' city water systems are an alternative to recirculation systems when splash pads are in a controlled environment with limited usage times or when systems and selected water play elements are designed for minimum water consumption. City water systems are a cost effective approach for a splash pad project when water consumption issues are not a concern. Water reclamation may be routed to a retention pond & used as means of irrigation.

City Water System

1 Activation Bollard

Touch post activator

2 Ground Spray

Flush spray feature with various nozzle effects

3 Drain to Waste Outlet

Main drain to collect all splash pad water to waste

4 Water Play Structures

Above grade spray feature with various water activities

5 Drain Line to Waste

Take waste water to storm sewer system or retention pond

6 Distribution Manifold

Pre-plumbed, pre-fabricated with winterization blow-out-port

7 Solenoid Valves

Optional on each feature line for sequencing of events

8 Manual Valves

Manually control each spray feature's spray height & distance

9 Main Solenoid Valve

On/Off control for splash pad main water supply

10 System Control Panel

Controls operational hours, duration of time, sequencing of events, & on/off controls.

11 Main Power Supply

Typically 120V, Single Phase, 60 Hz power feed

12 Main Water Supply

Municipal water supply with pressure regulator (20 to 30 PSI) & back-flow preventer

Optional Equipment

* Above or below grade equipment enclosures & water re-purpose reservoir

